



C-Carbide shank 錫鋼柄

H-Anti-vibration shank 抗震柄

V-Anti-vibration shank with coolant 抗震水孔柄

▼Screw Type:

Order No.	Insert	Dimensions(mm)					Parts				Wrench	
		柄徑 DCON	工作寬度 WF	長度 LF	最小加工徑 DMIN	頭長 LH	Shim R	Shim L	Key	Lock	Wrench	Wrench
SIR/L1010-11	11IR/L	10	5.2	150	10	25	-	-	-	CS25059	FT-8	-
SIR/L1012-11		12	5.2	150	10	25	-	-	-			-
SIR/L1210-11		10	6.3	150	12	25	-	-	-			-
SIR/L1412-11		12	7.5	150	14	25	-	-	-			-
SIR/L1216-11		16	6.3	150	12	25	-	-	-			-
SIR/L1516-11		16	7.5	150	15	25	-	-	-			-
SIR/L1516-16	16IR/L	16	8.2	150	15	35	-	-	-	CS35090	FT-15	-
SIR/L2016-16		16	10	150	20	35	-	-	-			-
SIR/L2420S-16		20	12	180	24	35	AI16	AE16	CSH0306	CS35117S		LW025
SIR/L3025S-16		25	15	200	30	35						LW025
SIR/L3732S-16		32	18.5	250	37	35						LW025
SIR/L4440S-16		40	22.5	300	44	35						LW025
SIR/L5550S-16		50	28.5	350	55	35						LW025
SIR/L6660S-16		60	33.5	400	66	40						LW025
SIR/L2420-22	22IR/L	20	13	180	24	35	-	-	-	CS40115	-	
SIR/L3025S-22		25	16	200	30	35	AI22	AE22	CSH0408		LW030	
SIR/L3732S-22		32	19.5	250	37	35					LW030	
SIR/L4440S-22		40	24.5	300	44	35					LW030	
SIR/L5550S-22		50	30.5	350	55	35					LW030	
SIR/L6660S-22		60	35.5	400	66	40					LW030	
SIR/L5550S-27	27IR/L	50	31.5	350	58	35				AI27	AE27	CSF5020
SIR/L6660S-27		60	36.5	400	68	40	-	LW030				
H05H-SIR06-06	06IR	5	3.5	100	6	10	-	-	-	CS20038	FT-6	-
H06H-SIR06-07		6	4.4	100	7.5	12	-	-	-			-
H08K-SIR08-09	08IR	8	5.3	125	9.5	15	-	-	-	CS20045	-	-
H10K-SIR11-12	11IR	10	6.7	125	12	18	-	-	-	CS25080	FT-8	-
C06H-SIR06-07	06IR	6	4.4	100	7.5	12	-	-	-	CS20038	FT-6	-
C08K-SIR08-09	08IR	8	5.3	125	9.5	15	-	-	-	CS20045		-
C10M-SIR11-12	11IR	10	6.3	150	12	18	-	-	-	CS25080	FT-8	-
C12Q-SIR11-14		12	7.7	180	14	25	-	-	-			-
C16R-SIR16-20	16IR	16	10	200	20	35	-	-	-	CS35090	FT-15	-

ER/IL: Left hand insert 左手刀片

IR/EL: Right hand insert 右手刀片